REVERSING CAMERA KIT (RCK070) AND ACCESSORIES





Supplied with 7" LCD monitor, 1/3" CMOS camera and 20 metre extension cable.



Main Features

- Voltage: 9-36V
- Rear-view camera meets IP68 rating
- Lens angle of 120°
- Operating temperature of -20°C to +50°C
- 18 IR Infrared LEDs for low light and night use
- 3 Camera input capacity
- Integral monitor speaker and camera microphone

ACCESSORIES



R DVR Recording systems now available.

Easy to use plug-in and go optional extras for the RCK range.



63201103

Standard rear view camera as supplied with RCK070 kit, can be used as secondary or tertiary inputs and complete with adjustable visor.

Dimensions: 80 x 75 x 70mm



63201107

Adjustable camera, ideal for use as a secondary camera and can be positioned anywhere on vehicle.

Dimensions: 80 x 63 x 56mm



63201106

Rear centre camera for use when loading & unloading, reversing and while vehicle is stationary.

Dimensions: 135 x 210 x 77mm



63201109 (10m) 63201110 (20m)

63201108 (5m)

5m, 10m & 20m extension cables, available for all vehicle sizes.



63201104 (left) 63201105 (right)

Left & right hand side cameras designed for safety when turning near pedestrians, cyclists and smaller vehicles.

Dimensions: 60 x 57 x 84mm



63201111 and 63201112

Adaptor cables for using new RCK accessories with the VPK range.



RCK Trailer Kit

Heavy duty and weatherproof connection to link trailer mounted camera to cab mounted monitor.